

1-28-00
Linda
B.

INSC

PARTICLE PRODUCTION APPARATUS

BACKGROUND OF THE INVENTION

5 The invention relates to the production of particles by the reaction of chemical compounds. More particularly, the invention relates to the formation of particles by chemical reaction within a reaction chamber designed for the production of commercial quantities of product.

10 There has been growing demand for solid state materials with dimensions in the range from 1 to 100 nanometers (nm). These nanoscale particles have been found to exhibit unusual chemical, mechanical, electrical, magnetic and optical properties that are different from the corresponding properties of the bulk material and conventional powders. These unusual
15 properties can be exploited in a number of applications.

One advantage of nanoparticles relative to larger particles is the increased surface area for a given weight of material. The surface area per weight
20 of nanoscale particles can be one or two orders of magnitude greater than the surface area per weight of conventional powders. This increase in surface area is desirable for a variety of applications such as those involving catalysis, hydrogen storage and electrical
25 capacitors.

Advances in a variety of fields have created a demand for many types of new materials. In particular, a variety of chemical powders can be used in many different processing contexts. Specifically, there
30 is considerable interest in the application of ultrafine or nanoscale powders that are particularly advantageous for a variety of applications involving small structures or high surface area materials. This demand for

00363634-072400

ultrafine chemical powders has resulted in the development of sophisticated techniques, such as laser pyrolysis, for the production of these powders.

SUMMARY OF THE INVENTION

5 In a first aspect, the invention pertains to a particle production apparatus comprising:

a reaction chamber;

10 a reactant inlet defining a reactant path through the reaction chamber, the reactant inlet being connected to a reactant delivery system; and

15 optical elements defining a light path through the reaction chamber that intersects the reactant path, where the light path through the reaction chamber does not follow a single straight line path.

In another aspect, the invention pertains to a particle production apparatus comprising:

20 a reaction chamber;

a reactant inlet defining a reactant path through the reaction chamber, the reactant inlet being connected to a reactant delivery system;

25 a light source; and

30 optical elements directing a light beam from the light source through the reaction chamber that intersects the reactant path, the optical elements comprising a focusing element and a collimating element.

In a further aspect, the invention pertains to a method of producing a collection of nanoscale particles having a selected average particle diameter.

60222073200

In particular, the method includes reacting a reactant stream within a reaction chamber with a light beam, where the average time of flight of the reactant stream through the light beam is selected by changing the properties of the light beam to produce the selected average particle diameter.

Moreover, the invention pertains to a particle production system comprising:

10 a plurality of reactant inlets configured to direct a reactant stream toward one or more product outlets; and
a particle collection apparatus connected to the one or more product outlets to collect the product particles generated by the reactants from the plurality of reactant inlets.

In addition, the invention pertains to a method of producing a mixture of particles, the method comprising:

20 supplying different reactant streams to two reactant inlets;
reacting the distinct reaction streams to produce two product particle streams, each with different product particle compositions; and
25 directing the two product particle streams to a single particle collector such that a mixture of product particles are collected.

30 In another aspect, the invention pertains to a particle production apparatus comprising:
a reaction chamber;
a reactant inlet generating a reactant stream through the reaction chamber, the

003361.07209

5

10

A method of selecting reaction conditions can be based on this particle production apparatus. The method includes selecting the reaction conditions to produce a selected measurement on a spectrometer in a particle
15 production apparatus, wherein the selected measurement is correlated with a reaction product property.

20

25

30

a reaction chamber having a reactant inlet connected to a reactant delivery apparatus oriented to produce a reactant stream within the reactant chamber;

an optical element positioned to direct a light beam along a light path through the reaction chamber intersecting the reactant stream; and

5 a tapered tube extending from the reaction chamber along the light path, the tube supporting the optical element, and the tube having a smaller cross sectional area at the connection to the reaction
10 chamber relative to the cross sectional area of the tube at the optical element.

In another aspect, the invention pertains to a particle production system comprising:

60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244

5

10

15

20

25

30

Fig. 11 is a sectional view of the reaction chamber of Fig. 10, taken along line 11-11.

Fig. 13 is a sectional view of the reaction
5 chamber of Fig. 12, taken along line 13-13.

Fig. 15 is a schematic, perspective view of a reaction chamber extended in two dimensions having a moveable reactant inlet nozzle, where hidden structure is depicted using phantom lines.

Fig. 17 is a schematic, perspective view of a reaction chamber with a reactant inlet and an outlet meeting commensurate with the walls of the reaction chamber.

Fig. 18B is a fragmentary, perspective view of
25 the joining of the inner walls of the reaction chamber
walls shown in Fig. 18A.

Fig. 19B is a fragmentary, perspective view of the joining of the inner walls of the reaction chamber of the reaction chamber walls shown in Fig. 19A.

Fig. 20 is a fragmentary, section view of the wall of the reaction chamber with a porous inner wall for the delivery of inert gas from an inert gas channel within the wall.

5 Fig. 21A is a fragmentary sectional view of the wall of the reaction chamber with notches in the inner wall for the delivery of inert gas into the reaction chamber from an inert gas channel within the wall.

10 Fig. 21B is a fragmentary side view of a section of an inner, reaction chamber wall with notches for the delivery of inert gas.

15 Fig. 22A is a fragmentary, sectional view of another alternative embodiment of the wall of the reaction chamber configured for inert gas delivery, in which the inner wall includes wall segments that are connected by spacers to form the inner wall. The cross section is taken through a section of chamber wall along a direction parallel to reactant flow in the chamber.

20 Fig. 22B is a fragmentary sectional view of the chamber wall shown in Fig. 22A, where the section is taken along line B-B.

25 Fig. 23 is a schematic, perspective view of an elongated reaction chamber in which the light beam path extends from the main chamber along extension tubes.

Fig. 24 is a fragmentary, perspective view of a light beam path through a tapered tube into the main chamber.

30 Fig. 25 is a schematic, perspective view of a light beam path, intersecting with a reactant stream, generated with a cylindrical lens window.

Fig. 26 is a schematic perspective view of a light beam path with an expanding spherical lens and collimating optics leading to a cylindrical lens.

6022207E3E60

5

10

beam path and telescopic lens system of Fig. 28A.

reaction system with two light sources.

15

20

of Fig. 31, taken along line 32-32.

25

30

reaction chambers connected to a manifold leading to a

collection apparatus, where the reaction chambers are oriented such that a single light beam passes through the three reaction chambers.

Fig. 36 is a fragmentary schematic, sectional view of a reaction chamber with a mass spectrometer and a particle size analyzer connected to the reaction chamber to sample the reactant stream and product particles, respectively, where the cross section is taken roughly through the center of the chamber. An enlargement of an embodiment of the sampler is shown in the insert.

Fig. 37 is a schematic, perspective view of a reaction chamber connected to two types of spectrometers.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A variety of features can be incorporated into the construction of a reaction system, such that the reaction system is suitable for the efficient production of commercial quantities of chemical powders. Some of these improved features relate specifically to chamber design while others relate to control of the reaction process. The general requirements for the production of commercial quantities of materials include a relatively large flux of reactants and a suitable approach for the collection of the products/particles. Thus, efficient delivery of reactants and efficient removal or product are part of the efficient overall reaction process. While producing a commercial quantity of chemical powders, product particles with highly uniform properties are desirable for certain applications, such as chemical-mechanical polishing. In preferred embodiments, the reaction systems are used for the production of nanoscale particles.

093634-073109

5

15

30

heat the reactants to drive the chemical reaction. For laser pyrolysis, the reactant stream includes one or more reactants as well as a separate light absorbing gas, if the reactants themselves do not absorb light sufficiently. The reaction product is quenched rapidly after the reactant/product stream leaves the light beam. In part due to the nonequilibrium nature of the laser pyrolysis process, highly uniform product particles are produced.

For the performance of laser pyrolysis, a suitable optical configuration preferably is integrated into the reaction chamber such that the light beam intersects with all or most of the reactant stream. Thus, a preferred configuration of the optical path necessarily depends on the configuration of the reaction chamber, and visa versa. The reaction zone is roughly the region of intersection of the light beam and the reactant stream.

The chemical reactions in the reaction chamber effectively take place in a vapor state although particles can be present, both initially in the reactant stream and subsequently formed as reaction products. The reactants can be delivered as either gases and/or aerosols. The use of an aerosol delivery apparatus provides for the use of a wider range of reactants. Liquids for delivery as an aerosol include liquid solutions, neat liquids and dispersions. For example, solid or liquid reactants can be dissolved into a solvent and delivered as an aerosol. Similarly, solids can be dispersed in a liquid for delivery as an aerosol. If a solvent is used to form an aerosol, the solvent generally is rapidly evaporated during or prior to the reaction.

5 The particles can be collected in a batch mode or in a
continuous mode. In batch mode, the reaction can be
continued until the particle collection apparatus
becomes full. In continuous mode, product can be
harvested from the collection apparatus while the
10 reaction continues to produce additional product.

In preferred embodiments, product particles are highly uniform. Thus, preferred embodiments of the reaction system maintain the uniformity of the product particles while providing for the production of commercial quantities of materials. Furthermore, properties within the reaction chamber can be controlled, precisely to ensure the production of materials that are more highly uniform than was possible without improved approaches for controlling reaction conditions. In particular, approaches are described to carefully control the uniformity of the light beam, the reaction temperature, the chamber pressure, the reactant flux and the light intensity.

25 Reaction systems are described that are
suitable for the synthesis of chemical powders. In
general, the reaction systems can be used to perform
effectively "gas phase" reactions where the reactants
are vapors and/or aerosols. The aerosols include
30 particles and/or droplets dispersed and entrained in a
gas flow. The reaction systems are particularly useful
for performing laser pyrolysis for the production of
nanoscale particles. In a laser pyrolysis apparatus, a
light absorbing compound, possibly one or more of the

5

10

15

20

30

pyrolysis chambers. The aerosol atomizers can be broadly classified as ultrasonic atomizers, which use an ultrasonic transducer to form the aerosol, electrical atomizers, which use electric fields to form the aerosol, or as mechanical atomizers, which use energy from one or more flowing fluids (liquids, gases, or supercritical fluids) themselves to form the aerosol. Uniformity of the aerosol assists with the production of a more uniform product, for example, nanoparticles with a narrow size distribution.

Improved aerosol delivery apparatuses for reactant systems are described further in copending and commonly assigned U.S. Patent Application Serial Number 09/188,670 to Gardner et al., entitled "Reactant Delivery Apparatuses," incorporated herein by reference. These aerosol delivery systems can be adapted for use in reaction systems not involving laser pyrolysis. Approaches are also described therein for the adaptation of aerosol delivery by a variety of approaches with a reaction chamber elongated in one dimension in the plane perpendicular to a reactant stream. Some of these approaches include, for example, using an elongated nozzle opening, placing columns of gas jets adjacent the aerosol nozzle, employing a plurality of aerosol nozzles and applying a combination thereof.

The relevant components of a reaction system of interest are shown schematically in Fig. 1. Reaction system 100 includes a reactant delivery apparatus 102, a reaction chamber 104 and a collection apparatus 106. For the performance of laser pyrolysis in preferred embodiments, reaction chamber 104 has a light beam path 108 intersecting with a reactant stream. Light beam path 108 originates from a light source 110. A controller 112 is used to monitor the reaction

09362634-072409
Sub 02

2. Reactant Delivery Apparatuses

5. Reactant delivery apparatus 102 is used to deliver gaseous and/or aerosol reactants into reaction chamber 104 in the form of a confined reactant stream. The reactant stream is generally configured to correspond to the structure of reaction chamber 104.

10 The reactant flow stream preferably fills most of the cross sectional area of the reaction chamber such that there is little volume of the reaction chamber that is not involved in the reactant/product flow. The reactant stream preferably is surrounded by shielding gas to

15 assist with confining the reactant stream. If the reactant stream fills most of the cross sectional area of the reaction chamber only a small volume of shielding gas is needed. Preferred structures for reaction chamber 104 are described further below. General

20 features of reactant delivery apparatus 102 can be described without reference to the particular structure of reaction chamber 104.

Laser pyrolysis is performed with one or more reactants. Each reactant generally contributes one or

more atoms to the final product. The reaction can be exothermic overall. In traditional laser pyrolysis, the heat contributed by the laser is sufficient to stimulate the reactants to initiate the reaction. The composition of the reactant stream is adjusted such that the atoms recombine to form the desired products. The rapid quench of the reaction as the reactant stream leaves the reaction zone produces a highly uniform product.

Various embodiments of reactant delivery apparatus 102 are suitable for the delivery of gaseous and/or aerosol reactants and other compounds along the reactant stream. Reactants and other compounds within the reactant stream can be mixed prior to introduction into the reaction chamber. Then, the reactants can be delivered through a single reactant inlet as a mixed stream of compounds.

Alternatively, the reactant stream can be completed within the reaction chamber by the mixture of two or more compounds, e.g., reactants. This can be accomplished through the use of a reactant delivery apparatus 102 with two reactant inlets for the passage of reactants to form a reactant stream in reaction chamber 104. Separate streams of compounds are generated by the inlets for mixing within the chamber. The reactant inlets form part of an injection nozzle for directing reactants into the reaction chamber along the reactant stream. The use of multiple inlets can be particularly advantageous when the reactants are violently reactive. The use of multiple inlets for strongly reactive reactants is described further in copending and commonly assigned U.S. Patent Application, Serial Number 09/266,202 to Reitz et al., entitled "Zinc Oxide Particles," incorporated herein by reference. Similarly, one or more reactants can be combined with a

~~Handwritten text, mostly illegible due to blurring.~~

5
10
15
20
25
30

Alternatively, carrier gas can be supplied directly from light absorber source 124 or inert gas source 126, as appropriate. The gases from the first reactant source 120 are mixed with gases from light absorber source 124 and/or inert gas source 126 by combining the gases in a single portion of tubing 128. The gases are combined a sufficient, but possibly relatively short, distance from reaction chamber 104 such that the gases become well mixed prior to their entrance into reaction chamber 104. The combined gas in tube 128 passes through a duct 130 into channel 132, which is in fluid communication with channel opening 134 (or 136, as shown in phantom lines).

A second reactant can be supplied from second reactant source 138, which can be a liquid reactant delivery apparatus, a solid reactant delivery apparatus, a gas cylinder or other suitable container or containers. If second reactant source 138 delivers a liquid or solid reactant, carrier gas from carrier gas source 122 or alternative source can be used to facilitate delivery of the reactant. As shown in Fig. 2, second reactant source 138 delivers a second reactant to duct 130 by way of tube 128. Alternatively, second reactant source 138 can deliver the second reactant to tube 140 for delivery through a second reactant inlet 142, as depicted with phantom lines in Fig. 2.

With alternative delivery through channel openings 136, 142, the first and second reactants are mixed within the reaction chamber after exiting from the reactant inlets. If more than two reactants are used, the additional reactants can similarly be delivered through a single channel inlet 134, through two openings 136, 142, or through more than two reactant inlets, as appropriate or desired. Mass flow controllers 144 can be used to regulate the flow of gases within the reactant delivery system of Fig. 2.

As noted above, the reactant stream can include one or more aerosols. The aerosols can be formed within reaction chamber 104 or outside of reaction chamber 104 prior to injection into reaction chamber 104. If the aerosols are produced prior to injection into reaction chamber 104, the aerosols can be introduced through reactant inlets comparable to those used for gaseous reactants, such as leading to channel opening 134 in Fig. 2.

Referring to Fig. 3, an alternative embodiment of reactant delivery apparatus 102 is shown for delivery

SubD3

Sub D3

5 of two aerosol reactants. Aerosol generators 146, 148 deliver aerosol into delivery tubes 150, 152, respectively. Delivery tubes 150, 152 deliver reactants to two openings 154, 156, respectively. Aerosol generators 146, 148 can operate based on a variety of principles. For example, the aerosol can be produced with an ultrasonic nozzle, with an electrostatic spray system, with a pressure-flow or simplex atomizer, with an effervescent atomizer or with a gas atomizer where
10 liquid is forced under significant pressure through a small orifice and fractured into particles by a colliding gas stream. Suitable ultrasonic nozzles can include piezoelectric transducers. Ultrasonic nozzles with piezoelectric transducers and suitable broadband
15 ultrasonic generators are available from Sono-Tek Corporation, Milton, NY, such as model 8700-120. Suitable aerosol generators are described further in copending and commonly assigned, U.S. Patent Application Serial No. 09/188,670 to Gardner et al., entitled
20 "Reactant Delivery Apparatuses," incorporated herein by reference.

Reactant gases, inert gases and/or light absorbing gases can be supplied according to any of a variety of configurations into delivery tubes 150, 152,
25 as desired, by way of gas sources 158, 160 and gas supply tubes 162, 164. Alternatively, one of the aerosol generators can be eliminated such that the reactant delivery apparatus delivers an aerosol and a gaseous reactant through openings 154, 156,
30 respectively.

Alternative embodiments can be based on variation of the embodiments of Fig. 3 to deliver reactants by way of a single channel opening 134. In these embodiments, there is a single delivery tube. The

00334103660

second aerosol generator can be eliminated or configured to deliver an aerosol into the same delivery tube as the first aerosol generator. Thus, these alternative embodiments can be used to deliver into reaction chamber 104, an aerosol reactant and a gaseous reactant, two aerosol reactants or more than two reactants with one or more aerosols through a single channel opening 134.

Referring to Fig. 4, another embodiment 170 of the reactant supply system 102 can be used to supply an aerosol. Reactant supply system 170 includes an outer nozzle 172 and an inner nozzle 174. Outer nozzle 172 has an upper channel 176 that leads to a rectangular outlet 178 at the top of outer nozzle 172, as shown in the insert in Fig. 4. Rectangular outlet 178 has suitable dimensions based on the size of the reaction chamber. Outer nozzle 172 includes a drain tube 180 in base plate 182. Drain tube 180 is used to remove condensed aerosol from outer nozzle 172. Inner nozzle 174 is secured to outer nozzle 171 at fitting 184.

Inner nozzle 174 is a gas atomizer, which is available from Spraying Systems, Wheaton, IL, such as model number 17310-12-1x8jj. The inner nozzle has about a 0.5 inch diameter and a 12.0 inch length. The top of the nozzle is a twin orifice internal mix atomizer 186 (0.055 in. gas orifice and 0.005 in. liquid orifice). Liquid is fed to the atomizer through tube 188, and gases for introduction into the reaction chamber are fed to the atomizer through tube 190. Interaction of the gas with the liquid assists with droplet formation.

Outer nozzle 182 and inner nozzle 184 are assembled concentrically. Outer nozzle 182 shapes the aerosol generated by inner nozzle 184 such that it has a flat rectangular cross section. In addition, outer nozzle 182 helps to achieve a uniform aerosol velocity

5

10

25

20

25

30

connected to mounts 238, 240, respectively. Mounts 238, 240 are secured to a base plate 242, which is secured to reaction chamber 104. Mounts 238, 240 are angled such that the aerosols generated by aerosol generators 234, 236 mix within reaction chamber 104. Carrier gases and/or additional reactants can be delivered along with the aerosols using carrier gas tubes 244, 246.

A variety of configurations of the reactant delivery apparatus 102 were described by reference to Figs. 2-6. Additional embodiments for the reactant delivery apparatus for a particular reaction chamber 104 can be constructed based on the disclosure herein to achieve desired objectives.

3. Reaction Chamber

The reactant inlet or inlets generally are configured to produce a reactant stream that covers a significant fraction of the cross sectional area of the reaction chamber 104. Reaction chamber 104 can have a variety of designs and features. In preferred embodiments, reaction chamber 104 provides for the production of commercial quantities of product particles. To produce commercial quantities of particles efficiently, the apparatus must produce particles at a high rate, preferably greater than about 1kg per hour. A large reactant flux and a high yield are needed to reach these high production rates. The design of reaction chamber 104 must account for a high reactant flux and high product yield.

Reaction chamber 104 can be produced from any reasonable, sturdy and inert materials. Preferred materials include corrosion resistant metals, such as stainless steel. Other preferred materials for reaction chamber 104 include ceramics such as alumina and quartz, plastics such as polypropylene, polyethylene and

polyvinylidene fluoride, and glasses such as borosilicate glasses. Plastic materials are generally appropriate for synthesizing materials at more moderate temperatures. Glasses and ceramics are particularly
5 suitable when high temperature materials are synthesized. The surfaces of the reaction chamber preferably are smooth for easy cleaning. The surfaces of the reaction chamber can be coated to impart corrosion resistance and/or to make the surfaces easier
10 to clean. Suitable coatings include, for example, polytetrafluoroethylene and epoxy based materials.

As noted above, the reaction chamber can be heated to reduce or eliminate condensation of reactants and products (such as water) onto the chamber walls. In
15 addition, the chamber can be heated to reduce forces driving product particles toward cooler chamber walls associated with the Soret effect. Heating can prevent condensation by other effects such as low velocities in the flow field near the chamber walls. Empirical
20 adjustments can be made to obtain the desired level of heating to reduce or eliminate the Soret effect. Preferably, the temperature of the delivery channels of the reactant delivery system, the inside of the reaction chamber and the collection system are at approximately
25 the same temperatures to avoid condensation.

For large fluxes of reactants, heating due to the reaction can result in the overheating of the walls, which can damage the reaction chamber. Thus, insulation and/or cooling of the walls may be desirable. Liquid
30 cooling of the reaction chamber can be accomplished by submerging the reaction chamber in a circulating liquid bath or connecting a water, oil or other liquid bath to a series of tubes flowing along the surface or within the reaction chamber. In preferred embodiments, the

003634 07249
66720 FEB 22 1966

Also, electrostatic repulsion can be used to reduce or eliminate contamination of the chamber walls with particles. Some particles may be charged from the reaction process. In this case, the chamber walls can be given a like charge to repel the particles. Alternatively, the particles can be charged. Referring to Fig. 1, high voltage electrodes 280, 282 can be used to charge the particles. Electrodes 280, 282 have opposite charges from each other. Electrodes 280, 282 preferably conform to the walls of the chamber to avoid distorting the flow through the chamber, and electrodes 280, 282 generally are separated from the chamber walls by an electrically insulating layer to prevent a short circuit of the electrodes. Negative electrode 280 can be heated to facilitate the projection of an electron beam. The chamber walls separate from electrodes 280, 282, or at least the upper portion 286 of the chamber, can be given a low charge opposite of the particle charge. For example, if the particles are given a negative charge by electrodes 280, 282, the upper chamber walls 286 can be given a negative charge to repel the particles. The charge on the walls to repel the particles should be low such that no charge is transferred to the particles.

Referring to Fig. 7, reaction chamber 104 generally includes a main chamber 300, a reactant inlet or inlets 302, a product outlet or outlets 304 and other optional features, such as optical elements and measurement devices. In preferred embodiments involving the performance of laser pyrolysis, reaction chamber 104

5

10

25

30

5

10

30

available along the length of the reactant stream. The width of reactant inlet 302 can be selected such that the width of the reactant stream roughly corresponds to the width of the light beam. Use of an elongated main chamber for particle production is described further in PCT publication WO 98/37961 to Bi et al., entitled "Efficient Production of Particles by Chemical Reaction," incorporated herein by reference.

Alternative embodiments of main chamber 300 use a light path which does not follow a single straight line through the reaction chamber. These embodiments may be particularly desirable when the reactant stream is strongly absorbing of light such that having an elongated chamber, as described above, may be problematic. This is useful where the reactant stream is wider than the light beam. For example, a zigzag path through the chamber can be used where the light is bent within main chamber 300 using reflectors or other optical elements. Throughout this application, reflectors include completely or partially reflective mirrors, corner cube reflectors and other reflective optical elements. Alternatively, the light path through the reaction chamber can involve multiple straight line paths that are split outside of the chamber or that originate from multiple light sources.

An alternative embodiment 320 of main chamber 300 that achieves a large reactant flux is shown in Figs. 8 and 9. Main chamber 320 includes two reflectors 322 and 324 that deflect a light beam 326 across the width, "w", of chamber 320, as shown in Fig. 9. Preferably, due to the width of the beam in the plane of the cross section in Fig. 9, reflected light beam 326 roughly fills a cross section of main chamber 320 except for a portion of the area near the walls holding optical

elements 308, 310. The width of the chamber is substantially larger than the width of an incident light beam directed into the chamber.

5 The angle of light beam 326 entering window 308 and/or the extent of light beam 326 can be adjusted accordingly, to essentially cover the cross section of main chamber 320. Reflectors 322, 324 can be produced from suitable materials to reflect the appropriate type of light radiation. For infrared light, suitable
10 reflectors 322, 324 include mirrors produced from, for example, silicon, molybdenum, copper and/or a thin gold layer. Molybdenum mirrors tend to be the most durable. The reflectors can have cylindrical curvature or symmetry, e.g., cylindrical mirrors, to focus the
15 thickness of the beam along the reactant flow as the beam is reflected back into the reaction chamber. Alternatively, the incident beam can be focused with a very long focal length. Cooling can be supplied to the reflectors to increase their durability. Also, the
20 reflectors can be placed behind a window such that contaminants within the chamber cannot contact the reflector. Contamination of the reflector generally results in the deterioration of the reflector.

25 An expanded reactant inlet 328 opens into main chamber 320. The width of reactant inlet 328 can extend essentially the entire width of main chamber 320, although smaller widths of reactant inlet 328 can be used to achieve the desired reactant flux and absorption of light. The length of reactant inlet 328 generally
30 corresponds roughly to the coverage of the light beam. Also, the length of reactant inlet 328 and/or main chamber 320 should provide the desired reactant flux, where a desired reactant flux yields a desired production rate and yield.

0026664-072400

Reactant inlet 328 is depicted in Fig. 8 as being generally rectangular although other shapes, such as circular, elliptical, and the like, can be used. The described shapes refer to the general shapes of the reactant inlet, while the edges and corners can involve slight irregularities, curvatures or oscillations without altering the general shape. The reflectors can be similarly shaped to match the general shape of the reactant inlet. For example, a main reaction chamber 340 with an expanded elliptical, especially round, reactant inlet 342, a corresponding elliptical outlet 344 and curved reflectors 346, 348 is shown schematically in Figs. 10 and 11. Reflectors 346, 348 direct a light beam 350 that covers a significant portion of the cross section of the circular main chamber 340. Reflectors 346, 348 can be curved in the direction along the flow of reactant to focus the thickness of the beam along the reactant flow as beam is reflected back into the chamber. Additional light beams or light beams with a different orientation can be used to obtain alternative coverage by the light beam or beams.

Another alternative embodiment 360 of main chamber 300 to achieving a large reactant flux is shown in Figs. 12 and 13. Main chamber 360 has the shape of a pie wedge with two straight sections of chamber wall and a curved section connecting the straight sections. A movable reflector 362 directs a light beam 364 directed through window 366. In the sectional view of Fig. 13, phantom lines indicate the opposite sweep of the reflector and corresponding light beam 364. Main chamber 360 includes appropriately shaped reactant inlets 368 and a reactant outlet 370. The curved wall can include curved reflectors to reflect the light back

into the chamber or a light absorber can be used as a beam dump. Preferred reflectors include mirrors formed by thin gold layers. A light absorber preferably is cooled to prevent damage, where cooling can be provided by a water bath or the like.

In operation, the reflector preferably moves or rotates over its range at a relatively rapid rate. In particular, the reflector should scan rapidly relative to the time for the reactants to travel through the reaction zone. Suitably rapid reflector motion can be accomplished with a solenoid, with a piezoelectric transducer attached to the reflector mount or with a rotating motor with a cam. The scan angle, based on chamber design, and the scanning frequency can be selected to obtain desired coverage of the chamber with the laser beam. Preferably, a high scan frequency is used to obtain better coverage of the chamber. Suitable reflector materials are described above. Generally, for high intensity light, the reflector should be cooled. Window 308 provides for a light beam that strikes the reflector at a suitable angle to reflect the light over the desired range.

With any of the possible embodiments having a high reactant flux and an extended reaction chamber, a plurality of reactant nozzles can be used to supply desired reactants at desired reactant fluxes. For example, three reactant nozzles 374 are depicted in phantom lines in Fig. 12, leading to three reactant inlets 368. Alternatively, two, four or more nozzles can be used. Reactant inlets 368 overall cover the desired cross section of reactant chamber 360.

Different reactants can be directed to one or more nozzles 374 of the reaction chamber of Fig. 12. If inlets 368 are configured for little, if any, mixing of

092231-072400

the reactants from the different inlets, two or three distinct reactions yielding distinct products can be exploited. Mixing can be reduced or eliminated by supplying shielding gas between the flow from the different inlets. The reaction products can be combined within the collection system to form a desired blend. Similarly, a two inlet configuration for the elongated reaction chamber design of Fig. 7 is shown in Fig. 14. A first inlet 376 is located adjacent to a second inlet 378.

To take advantage of an extended reaction chamber to produce a high reactant flux, a reactant nozzle can be used that pivots. Thus, a reactant nozzle having a reactant inlet can move to fill the selected portion of the reaction chamber with reactant. A higher reactant velocity can be obtained using a smaller reactant inlet without needing to raise the pressure in other parts of the reactant delivery apparatus to correspondingly higher values. For example, in Fig. 15 a pivoting nozzle 382 has been adapted for use with the reaction chamber depicted in Fig. 8. A reactant inlet 384 is located at the end of pivoting reactant nozzle 382. Pivoting nozzle 382 pivots around pivot 386. Pivoting nozzles can be similarly adapted for other chamber shapes that are extended in one or two dimensions.

The flight time of the reactant stream through the light beam can affect the properties of the product particles formed by laser pyrolysis. The flight time can be altered by changing the flow rate through the reaction chamber. Alternatively, the flight time can be altered by changing the light beam thickness, as described further below. Also, the flight time of the reactants through the light beam can be extended by

changing the angle of the reactant stream relative to the propagation direction of the light beam.

Referring to Fig. 16, slanted light beam 390 enters main chamber 300 through displaced window 392 and strikes displaced optical element 394. The flight time is extended roughly by $1/\cos \theta$, as long as θ is not close to $\pi/2$. In the limit that the light beam is approximately oriented along the reactant path, the flight time reaches a limiting value determined by the path length over which the light beam and the reactant flow overlap before they are deflected away from each other. To obtain a desired angle between the light beam and the reactant stream, the reaction chamber, the light beam or both can be tilted relative to each other.

While reactant inlet 302 can be associated with a reactant nozzle projecting into main chamber 300, the nozzle can be eliminated such that the reactant inlet is flush with the corresponding wall of main chamber 300. Similarly, a reactant inlet 400 can span the entire bottom of main chamber 300, as shown in Fig. 17, with reactant inlet 400 attached to reactant delivery system 102 at flange 406. Reactant inlet 400 and outlet 402 are located at the ends of pipe shaped main chamber 404. Outlet 402 connects with collection apparatus 106 at flange 410. Although depicted in Fig. 17 as circular, main chamber 404 can have other cross sectional shapes, such as rectangular, square and elliptical, as desired. The optical path can be selected according to the shape of main chamber 404.

Main chamber 404 has the advantage of ease of construction since the main chamber does not have to be matched with a nozzle. To some extent, the precise boundaries of this embodiment of reaction chamber 300 holding the reaction zone are arbitrary. At some point,

though, the collection system and reactant delivery system will have functional components that clearly delimit the reactant delivery system and the collection system from any possible boundary for the reaction chamber.

4. Contamination Prevention

In any of the embodiments, reactants and product particles can contaminate chamber walls and optical elements. Also, contaminants in the reaction chamber can contaminate later products such that the later products lack desired levels of uniformity. Referring to Fig. 7, to reduce the spread of reactants and products from the reactant/product stream flowing from reactant inlet 302 to outlet 304, reaction chamber 104 preferably includes a shielding gas supply system. In preferred embodiments, shielding gas forms a blanket around the reactant stream within reaction chamber 104. The shielding gas preferably is an inert gas, although a reactant, such as oxygen, can be included with the inert gas such that a portion of the reactant can mix with the remaining portion of the reactant stream. Suitable inert gases may depend on the specific reaction being performed in the reaction chamber 104. Generally, suitable inert gases include, for example, argon, helium, and nitrogen.

In Fig. 7, a shielding gas inlet 440 is located between nozzle 314 and the wall of main chamber 300. In this way, shielding gas is delivered on all sides of the reactant stream. Shielding gas channel 442 feeds into shielding gas inlet 440. Shielding gas channel 442 connects with a shielding gas source that can be a pressurized gas cylinder, a liquified gas supply or the like. A variety of alternative configurations can be used for the shielding gas inlet,

as desired. For example, a configuration of a shielding gas inlet 444 for a two inlet elongated chamber design is depicted in Fig. 14. Shielding gas is directed between reactant inlets 376, 378 such that independent reactions can be performed. Alternatively, no shielding gas can be directed between inlets 376, 378 if equivalent reactants are directed through each inlet. Furthermore, the shielding gas inlet can be configured for different shapes of main chamber 300 and the corresponding inlet 302, such as those shown in Figs. 8-13 and 17.

In alternative embodiments, shielding gas is delivered through small openings or pores in the chamber walls. Preferably, the volume of shielding gas is kept low to reduce cost. For example, approaches used for cooling the walls of turbine combustors, such as thin film cooling techniques, can be adapted for the delivery of shielding gas. The idea is to deliver a thin film of shielding gas along the walls of the reaction chamber.

Referring to Figs. 18A and 18B, a first approach for thin film shielding gas delivery is depicted. The chamber walls include an outer wall 412. The inner chamber wall includes two or more overlapping sections, including first section 414 and second section 416, which extend around the circumference of the reaction chamber to form the inner wall of the reaction chamber. First section 414 has a smaller diameter around the circumference of the reaction chamber compared with second section 416 such that they can overlap as shown in Figs. 18 and 19. A delivery channel 418 is located between outer wall 412 and inner walls 414, 416. Delivery channel 418 is connected to a source of inert shielding gas. Inner wall 416 includes a bend 420 to connect to flange 422 that is welded or otherwise

secured against inner wall 414. The overlapping region between inner walls 414, 416 forms a channel 424 that directs a thin film of shielding gas along inner wall 416. Shielding gas passes into channel 424 through openings 426.

An alternative embodiment of a thin film system is shown in Figs. 19A and 19B. In this embodiment, openings 430 are located along bend 420 such that shielding gas impinges on inner wall 414 to distribute flow within channel 424 so that flow is more or less uniform as it exits channel 424 along inner wall 416. While the flow arrows in Figs. 18A and 19A indicate an overall flow within delivery channel 418 from left-to-right, the flow within delivery channel 418 can be in the opposite direction from right-to-left. The pressure in delivery channel 418 is higher than the pressure in the reaction chamber such that inert gas flows into channel 424. If a plurality of film delivery channels 424 are used, as described below, the flow arrows within delivery channel 418 can have different relative directions for different sets of channels 424 combination if the inlet of shielding gas is between two sets of openings 426 or 430.

In Figs. 18-19 only one film directing channel 424 extending the circumference of the reaction chamber is shown. Additional film directing channels can be formed along the direction of flow within the reaction chamber using additional sections of inner wall, if desired for the efficient delivery of shielding gas. These series of channels 424, each extending around the circumference of the reaction chamber, preferably are repeated along the length of the chamber to the collector. In preferred embodiments, flow from the reaction chamber is directed to the collector along the

093634.072499

inner walls of the reaction chamber form a part of an outlet into the collection system without a distinct channel 316 constricting the flow from the reaction chamber to conduit 318, as shown in Fig. 7. If the inner walls of the chamber smoothly connect to conduit 318, the series of channel 424 can continue into conduit 318 until the processing part of the collector is reached.

In another alternative embodiment, the chamber walls along the direction of the reactant flow include an inert gas channel 700 between an inner wall 702 and an outer wall 704, as shown in Fig. 20. All or a portion of inner wall 702 is a porous metal such that inert gas permeates into the interior of the reaction chamber. Thus, a film of inert gas lines the porous metal along the wall of the reaction chamber.

In a similar embodiment, the chamber walls include an inert gas channel 710 between an inner wall 712 and an outer wall 714, as shown in Figs. 21A and 21B. Inner wall 712 is formed from stamped metal that has louvers 716 along inner wall 712 that form openings through inner wall 712. Some inert gas flowing within channel 710 flows through louvers 716 into the reaction chamber along inner wall 712. Additional variations on the this approach can be used to deliver a thin film of shielding gas along the inner wall of the reaction chamber.

A further alternative embodiment is shown in Figs. 22A and 22B. The shielding gas delivery conduit 730 is formed by outer wall 732 and inner wall 734. Inner wall 734 is formed by a series of wall sections 736. Each wall section 736 extends around the circumference of the reaction chamber. Wall sections are secured to adjacent sections by spacers 738 to form

5 While window 308 and optical element 310 are shown in Fig. 7 along the wall of main chamber 300, window 308 and optical element 310 are displaced away from the wall of main chamber 300, in some preferred embodiments. Referring to Fig. 23, tubes 436, 438
10 displace, respectively, window 308 and optical element 310 from main chamber 300. Window 308 and optical element 310 are located, respectively, near the end of tubes 436, 438 away from the reactant stream.

Alternatively, especially if optical element 310 is a beam dump, optical element 310 can be placed

flush with the chamber wall without use of a tube 438. Beam dumps are designed to absorb the energy from the radiation. Thus, a beam dump is not as sensitive to contamination by reactants or products within chamber 300. In another alternative embodiment, both window 308 and optical element 310 are placed on the reactor wall with little or no displacement away from the reactor wall. In this configuration, sufficient shielding gas should be used to prevent contamination of window 308 and/or optical element 310.

It may be advantageous to use a tapered tube 442, as shown in Fig. 24. With this configuration, the opening between tube 442 and reaction chamber 300 is smaller than window 308. The taper of tube 442 results in higher inert gas velocity at the opening of tube 442 into main chamber 300 for a given inert gas pressure in inlet 440. If the light directed through the tube into the chamber is focused, the shape of the tube can account for the changing diameter of the light beam. Optical component 310 may or may not be mounted on a corresponding tapered tube, depending on the nature of the beam focus, the nature of optical component, and other design considerations.

Window 308 and optical element 310 can be mounted onto main chamber 300 or onto tubes 436, 438, respectively, with a vacuum o-ring seal or by fusing the lens directly into the stainless steel flanges. Alternatively, the radiation source can be located within tubular member 436.

5. Optics and Light Beam Control

Window 308 provides for the entrance of the light beam into reaction chamber 104, while reaction chamber 104 is sealed from the ambient atmosphere. Window 308 can be a planar window that transmits a

0975631-072409

significant amount of the incident light radiation over a desired frequency range. Alternatively, window 308 can be a lens that focuses the transmitted light. Furthermore, window 308 can be a component of the light source, such as the partly reflective output coupler or mirror of a laser.

Referring to Fig. 25, in certain preferred embodiments, window 308 is a cylindrical lens 450 that focuses the thickness of light beam 452 roughly in the center of main chamber 300 without changing the width of light beam 452. The width "b" of light beam 452 is oriented perpendicular to the propagation direction of reactant stream 454. Using a cylindrical lens has the disadvantage that the flight time of reactant stream 454 through light beam 452 generally is different at different points with different thicknesses along light beam 452. This variation in the thicknesses due to focusing with a cylindrical lens can be reduced by changing the depth of field and by introducing spherical aberrations. However, a cylindrical lens can produce a narrow light beam within the reaction zone. Alternatively, window 308 can be a plano, i.e. flat, window, and a cylindrical lens can be placed at another point between the light source and the reaction zone, where the light beam intersects the reactant stream.

In an alternative embodiment, as depicted in Fig. 26, the beam is first expanded with a spherical lens 454 and collimated with collimating optics 456 prior to a cylindrical lens 458. Expansion and collimation of the beam provides a wider width "w" to accommodate a wider reaction chamber and reactant inlet or inlets with a correspondingly larger reactant flux.

An alternative way of accommodating a wider reaction chamber/reactant inlet involves the use of a

beam splitter. Referring to Fig. 27A, a beam splitter 460 splits the incident beam into two components. A reflector 462 is used to direct the second beam, as desired. Generally, the second beam is directed parallel to the transmitted first beam to provide an effective wider beam through the reaction chamber. The second beam can be directed to a second reaction chamber. Focusing optics can be placed as desired along one or both beams.

As an alternative to using a beam splitter, two reflectors 464, 466 can be used to reflect the beam parallel to the incident beam in the opposite direction but displaced slightly from the incident beam, as shown in Fig. 27B. For example, the first reflector 464 can be placed at 45 degrees relative to the incident beam with the second reflector 466 being at 90 degrees relative to the first reflector. Reflectors 464, 466 may or may be curved reflectors, which focus the beam. For example, reflector 466 can be a cylindrical mirror that focuses the thickness of the beam at the center of the reaction chamber. Thus, the reflected beam effectively widens the reaction zone. Other optical elements can be included along with the two reflectors. The reflected beam can be directed to a beam dump or further optics to redirect the beam. Using either a beam splitter or a displaced reflected beam, the two approximately parallel beams may or may not overlap.

In an alternative preferred embodiment, collimating optics are used to compress (or expand) the beam thickness. For example, suitable collimating optics can comprise telescope optics, as shown in Figs. 28A and 28B. In Figs. 28A and 28B, two cylindrical lenses 470, 472 are used to narrow the thickness of light beam 474 along the direction of propagation of

reactant stream 476. Cylindrical lens 470 is a positive (focusing) cylindrical lens. Cylindrical lens 472 is a negative (defocusing) lens placed a distance from cylindrical lens 470 of less than one focal length of cylindrical lens 470. The focal lengths of cylindrical lenses 470, 472 and the distance between cylindrical lenses 470, 472 can be determined based on the desired thickness of light beam 474 in the reaction zone using standard optics principles.

Additional lenses can be used to control aberrations, diffraction based spreading of the beam, focusing, and other optical properties of the beam for the embodiment in Figs. 28A and 28B. Referring to Fig. 7, either lens 470, 472 can serve as window 308, although generally as many of the optical elements are placed outside of reaction chamber 104 as possible to reduce contamination of the optical elements. Both lenses 470, 472 can be placed inside or outside of reaction chamber 104, and window 308 can be a planar, nonfocusing window.

The optical configuration in Figs. 28A and 28B can be used to obtain a more uniform light beam across the reaction zone. In particular, the light beam in the reaction zone preferably has a maximum thickness in the direction along the reactant flow no more than a factor of ten greater than the minimum thickness, more preferably no more than a factor of five and even more preferably no more than a factor of two greater than the minimum thickness. Since the time of flight of the reactants through the light beam generally is more uniform with telescopic optics as shown in Figs. 28A and 28B, the product particles may have correspondingly more uniform properties. In particular, the use of telescopic optics to adjust the beam may result in a

5

15

25

30

5

10

25

30

sources 110, 480 are aligned with each other. If light sources 110, 480 are lasers, the laser optics should not be damaged if two beams are collinearly aligned, assuming that the beams do not spread significantly. If
5 light sources 110, 480 are roughly equivalent with respect to frequency and intensity, the use of two light sources 110, 480 leads to a more uniform light intensity within the reaction zone. Multiple reaction chambers can be located between light source 110 and light source
10 480. Alternatively, light sources 110 and 480 can be displaced in the horizontal or vertical directions.

Light sources 110, 480 can be lasers or conventional light sources. Similarly, light sources 110, 480 can be monochromatic or polychromatic. Light
15 sources 110, 480 can produce light in any portion of the optical spectrum ranging from infrared frequencies to ultraviolet frequencies. Over this frequency range, the light is optical radiation that can be manipulated using conventional optical elements such as reflectors and
20 lenses. Preferred embodiments for light sources 110, 480 include infrared lasers, such as CO₂ lasers and YAG lasers, and ultraviolet lasers, such as eximer lasers and pumped dye lasers tuned to photodissociate one or more reactants. With ultraviolet light, the windows
25 into and out from the reaction chamber can be made from quartz. Ultraviolet light with appropriately selected frequencies can be used to drive various reactions that may or may not be of a pyrolytic nature. For example, ultraviolet light can be used to form oxygen radicals
30 from molecular oxygen. Oxygen radicals are a powerful oxidizing agent. In addition, ultraviolet light can drive the polymerization of organic compounds.

6. Collection System

003634.0349
66720.723260

Alternatively, collection system 106 and reactant delivery system 102 can be reversed such that product is collected from the bottom of reactant system 100 and reactants are delivered from the top, where the flow helps to compensate for possible buoyancy of the particles. Similarly, the entire apparatus can be rotated about 90° such that the reactant stream is projected horizontally. A horizontal orientation can be helpful for very high throughputs.

reaction chamber at an angle relative to the vertical arrangement shown in Fig. 7. In one preferred embodiment, reaction chamber 480 is placed at an angle, as shown in Fig. 30. Reaction chamber 480 is connected to a reactant delivery apparatus 482 and a particle collection apparatus 484. Since reaction chamber 480 is at an angle, a curved channel is not needed between reaction chamber 480 and particle collector 484. Removal of the curved channel may improve the flow properties through the system.

25 Reactant system 100 can be designed for
operation in a batch mode or a continuous mode. In a
batch mode, the reaction must be terminated or suspended
in order to harvest the product particles. In
continuous mode, product particles can be harvested
30 while particle production and collection continues. For
example, continuous particle collection can be
accomplished by diverting flow from one batch type
collector to a second batch type collector, such that
the first collector can be replaced while the second is

used to collect product particles. A variety of collection system configurations can be used for either batch or continuous operation.

For batch operation, a convenient
5 configuration of the collection system includes a filter
in the flow that traps a substantial amount of the
product particles. An embodiment of a collection system
500 with an elongated reaction chamber and a batch
collection system is depicted in Figs. 31 and 32. The
10 outlet of reaction chamber 500 leads at its top to a
curved channel 502. Preferred collection systems
include a curved channel, especially when the collection
system is mounted at the top of the reaction chamber
such that the particles are not collected directly above
15 the reaction chamber.

In the embodiment shown in Figs. 31 and 32, a
cylindrical filter 506 is located in the flow path
between reaction chamber 500 and exhaust 504.
Cylindrical filter 506 is mounted at seal 508. Cap 510
20 is located at the end of cylindrical filter 506.
Exhaust 504 generally is connected to a pump or the like
to maintain the pressure within reaction chamber 500 at
a desired pressure. The collection of manganese oxide
nanoparticles using a reaction chamber and collection
25 system essentially as depicted in Figs. 31 and 32 is
described in copending and commonly assigned U.S. Patent
Application 09/188,770 to Kumar et al., entitled "Metal
Oxide Particles," incorporated herein by reference.

A collection apparatus 520 for continuous
particle collection is depicted in Fig. 33. Collection
apparatus 520 includes a tank 522 and a plurality of
filters 524. Filters 524 block flow paths from inlet
526 to exhaust 528. Exhaust 528 generally is attached
to a pump or the like to maintain the pressure with tank

667220" F2329260

Sub
FI

Sub 5

522 at desired values. Reaction chamber 530 is attached to a channel 532 that connects to inlet 526. A burst of air or a mechanical vibration is delivered to filters 524 to dislodge particles. Dislodged particles fall through valve 534 for collection in a container 536. Valve 534 can be closed to allow replacement or emptying of container 536, when it is full. A second reaction chamber 540 can be attached to collection apparatus 520 by way of channel 542. The improved collection apparatus shown in Fig. 33 is described further in copending and commonly assigned U.S. Patent Application Serial Number 09/107,729 to Gardner et al., entitled "Particle Collection Apparatus and Associated Methods," incorporated herein by reference.

To produce different product particles, a plurality of reaction chambers 550 can be connected in parallel, as shown in Fig. 34. The number of reaction chambers can be two, three, four or more, as desired. The particles produced in different reaction chambers 550 may or may not differ in composition and/or particle properties, such as size, as desired. For certain applications it may be desirable to have mixtures of particle collections in which each collection is highly uniform. The chambers have curved channels 552 that feed into a manifold 554. Manifold 554 leads to a particle collection system 556. The different particles mix in manifold 554 and mix further in collection system 556 such that a particle mixture is collected in container 558.

As noted above, a light beam can be directed sequentially through a series of reaction chambers. The product of each reaction chamber can be separately collected for use. In an embodiment shown in Fig. 35, a plurality of reaction chambers 570 is arranged such

Subcs

003531 030
667220 FEB 92

that a single light beam path 572 extends through multiple reaction chambers 570. The chambers can be in a line or in an alternative relationship with appropriate optics to direct the light beam from chamber to chamber. The number of reaction chambers can be selected as desired if sufficient light intensity is available. This embodiment can be particularly useful if subsequent reactions require a lower light intensity than reactions in chambers placed at prior positions along the light beam. Thus, light beam 572 that is attenuated by passage through one reaction chamber 570 subsequently passes through another reaction chamber 570 such that efficient use is made of light beam 572. Reaction chambers 570 lead to a manifold 574 for the mixture of the product particles and for the direction of the particles into particle collector 576. The mixture of product particles is collected in container 578. Light beam 572 can terminate at beam dump 580.

7. Control of the Reaction System

Referring to Fig. 1, controller 112 preferably includes a computer processor. The computer processor preferably is incorporated into a personal computer although various work stations, main frame computers or custom designed dedicated processors can be used. The computer processor can use a Windows®, MacIntosh®, UNIX®, or other reasonable operating system. The computer can run commercial control system software appropriately programmed to operate the particular system. Suitable control software includes LABVIEW®. Controller 112 preferably is connected by suitable parallel or serial connections 590 to reactant delivery system 102, reaction chamber 104, collection apparatus 106, and/or laser 110.

With respect to control of the reaction system, the various system parameters can be controlled to achieve very uniform reaction conditions. During the formation of commercial quantities of particles, the reaction system may be operated for extended period of time over which there is additional opportunity for reaction parameters to vary. Therefore, the development of improved approaches to control reaction conditions can be used to maintain product uniformity over an extended production run.

In addition, by further improving the uniformity of the reaction conditions, it is possible to form more highly uniform product particles. As noted above, one approach to obtaining more highly uniform particles involves the use of optics that produce a laser beam path within the reaction chamber that has a more uniform thickness through the reaction zone. Thus, improved control approaches can be used to maintain the uniformity of the reaction conditions over extended periods of time, as well as improving the uniformity of the reaction conditions within the reaction chamber to produce a more uniform product than could be achievable before. A second goal is to use information regarding the reaction to assist with the selection of suitable reaction conditions to produce desired product particles.

A variety of reaction parameters influences the characteristics of product particles produced in a laser pyrolysis chamber. The chamber pressure can be varied with a valve leading from the reaction chamber to a pump. Generally, a pump or fan is needed regardless of the desired value of the reaction pressure since the flux of material must be maintained through the chamber, although the back pressure of the reactants and

09362634.072499

shielding gases can, in principle, maintain a desired flux.

5 The pressure in the reaction chamber generally is measured with a pressure gauge. For example, a manometer can be used as a pressure gauge. Manometers provide accurate linear responses with respect to pressure. In preferred embodiments, the pressure gauge is connected to controller 112. Controller 112 can be used to monitor the pressure in reaction chamber 104 and
10 maintain the pressure in reaction chamber 104 within a specified range using a feedback loop with the collection system. The operation of the feedback loop depends on the structural design of the collection system, and may involve, for example, the adjustment of
15 a valve, pump speed and/or filter pulsing rates.

Referring to Fig. 1, collection system 106 generally includes a pump 590 and a valve 592 leading to the pump. Controller 112 can adjust the opening of the valve or the pumping rate, as part of a feedback loop
20 with the chamber pressure. Suitable automatic valves for interfacing with controller 112 are available from Edwards Vacuum Products, Wilmington, MA. If manual valves are used, controller 112 can notify an operator to adjust the manual valve appropriately.

25 Similarly, controller 112 can adjust other parameters within collection apparatus 106. For example, if collection apparatus 106 includes multiple collection ports, controller 112 can switch between two ports when a filter or other collection vessel accessed
30 through one port is so full of product that pressure cannot be maintained. Alternatively, with the collection apparatus shown in Fig. 33, the pulse parameters for pulsing the filters can be altered to improve the pressure consistency in the reaction

156 F2240 F229260

chamber. The pressure differential across the filter can also be monitored. Similarly, other parameters of the collection apparatus can be adjusted by controller 112, as appropriate.

5 Besides maintaining the chamber pressure at a desired value, it is desirable to maintain the relative amounts of the reactants to be constant. While in principle the flow of each reactant can be measured, it is difficult to obtain an extremely accurate mass flow
10 reading, especially with aerosol reactants. Alternatively, a small portion of the reactant stream can be removed for evaluation. Referring to Fig. 36, reactant inlet 600 directs a reactant stream into reaction chamber 602. A small sampler, spoon or tube
15 604 directs a small portion of the reactant stream to a mass spectrometer 608, such as a quadrupole mass spectrometer. The mass of the reactants are evaluated to determine the flux of reactants in the reactant stream. The measurements of the mass spectrometer can
20 be used in a feedback loop to regulate the flow of reactants using controller 112 or another processor. The feed into the mass spectrometer preferably includes a filter to remove any particles from the stream. For aerosol reactants, the droplet size can be measured
25 optically through a window directed toward the reactant stream. The atomizer parameters, such as pressure, flow, etc., can be adjusted in a feedback loop to maintain a desired droplet size in the reactant stream.

 Similarly, reaction chamber 602 can include a
30 particle sampler 610 to draw a small portion of the product particles from reaction chamber 602. Particle sampler 610 is located down stream from reaction zone 612. Sampler 610 connects with a particle size analyzer 614. Suitable particle size analyzers include, for

66729 FEB 96

example, a Microtrac UPA instrument from Honeywell based on dynamic light scattering and ZetaSizer Series of instruments from Malvern based on Photon Correlation Spectroscopy. The sampled particles are deposited into
5 a liquid for the performance of the particle size analysis by these approaches. Particle size analyzer 614 also can be connected to controller 112 or to a separate processor such that the information on particle size can be used to control the reaction conditions.

10 The conditions in the reaction zone can be directly monitored to ensure that the heat and other forms of energy in the reaction zone remains relatively constant. To monitor the heat and other forms of energy as well as the characteristics of the chemical species
15 in the reaction zone, a spectrometer, preferably a spectrophotometer, can be used to monitor the electromagnetic emissions from the reaction zone. A spectrophotometer is an instrument that measures the intensity of radiation at a plurality of frequencies, generally many frequencies and preferably greater than
20 10. Referring to Fig. 37, a light monitor 620 is mounted on elongated reaction chamber 622. For preferred embodiments with an infrared light source, light monitor 620 is an infrared monitor. An infrared
25 monitor can include a filter to pass only infrared light and a photodetector sensitive only to infrared light. Alternatively, an infrared monitor can include a grating or prism to spread the infrared light to provide for frequency dependent measurements. The frequency
30 dependent measurements can be used to evaluate the heat absorption in the reaction zone. Alternatively, the measurements of a light meter can be used for adjustment of laser intensity assuming that the reactant flux and other reaction conditions are constant. The laser

intensity can be adjusted also based on measurements of pressure and/or reactant flow rates.

5 The heat in the reaction zone can be adjusted by altering the laser intensity, the concentration of inert compounds, such as argon, or the concentration of laser absorbing material. In particular, fluctuations in the light intensity measurements can be used to regulate the light source intensity. For example, if infrared measurements drop, the light source intensity can be increased to return the infrared intensity to nominal values, and vice versa. This approach is especially useful as part of a complete monitoring program such that fluctuations in the light intensity can be attributed to light fluctuations rather than reactant flux variations. The adjustment of light intensity can be performed using controller 112 interfaced with light source 110.

10 While laser pyrolysis tends to produce highly uniform product particles, with the combination of features described herein including the regulation of total pressure, reactant flux and light source intensity, the uniformity of the product particles can be increased further. This regulation of reaction parameters may be especially important for the production of commercial quantities of particles so that the product properties do not vary significantly with time during a production run. Furthermore, for certain applications the uniformity of the particles may be critical. Thus, approaches that can increase the uniformity of the product particles to even higher standards can have important commercial ramifications.

20 The nature of the product particles depends on the reaction conditions. Certain materials have extremely varied and complex phase diagrams that may

09362671.072409

involve several different oxidation states and a variety of crystal structures. In addition, the physical properties of the particles can vary. It can be painstaking work to correlate the reaction conditions with the properties of the product particles. Any approach to facilitate this process would be extremely valuable.

An efficient approach to correlate reaction conditions with product particle properties makes use of an infrared, visible and/or UV spectrometer 624, preferably a spectrophotometer, mounted on reaction chamber 622. Spectrometer 624 can be designed to measure light from the reaction zone, where the light beam intersects the reactant stream, or the region just outside of the reaction zone, where the reaction products are emitting light during their quench. In either case, the spectral features of the emissions can be correlated with the properties of the product particles. The emissions from the reaction zone, the product particles and/or the reactive species are indicative of the reactions taking place and the products being formed. Alternatively, the spectrometer can be used to measure absorption or raman scattering by the reactant stream, at the reaction zone or before or after the reaction zone. Using emissions, absorptions and/or scattering frequencies, the phase diagram as a function of reaction parameters can be mapped out in a systematic way.

Then, the correlation between optical properties, such as spectral features due to emission, absorption and/or raman scattering, and product properties can be used to adjust reaction conditions within a particular reaction chamber. Relevant reaction conditions include, for example, chamber pressure,

5

10

20

25